

## Clips ASFA



### Technical information:

Stock items – versions W1 ir W4. W1 – band, housing and screw – carbon steel zinc-plated. W4 – band, housing and screw – stainless steel 1.4031 (AISI304).

**Standard:** DIN3017

Code	Application, mm	Working pressure, bar	Code	Application, mm	Working pressure, bar
CW-08-12-W1*	08-12	45	CW-90-110-W1	90-110	8
CW-08-16-W1	08-16	43	CW-100-120-W1	100-120	6
CW-10-16-W1*	10-16	43	CW-110-130-W1	110-130	5
CW-12-22-W1	12-22	36	CW-120-140-W1	120-140	5
CW-16-27-W1	16-27	36	CW-130-150-W1	130-150	4
CW-20-32-W1	20-32	36	CW-140-160-W1	140-160	3
CW-25-40-W1	25-40	26	CW-150-170-W1	150-170	2
CW-32-50-W1	32-50	22	CW-160-180-W1	160-180	2
CW-40-60-W1	40-60	16	CW-170-190-W1	170-190	1,6
CW-50-70-W1	50-70	12	CW-180-200-W1*	180-200	1,6
CW-60-80-W1	60-80	10	CW-200-220-W1*	200-220	1,6
CW-70-90-W1	70-90	9	CW-210-230-W1*	210-230	1,6
			CW-220-240-W1*	220-240	1,2

\*-not stock

HIDROBALT  
*Quality and reliability since 1995..*