

## 350AA

**Steam 6 bar, hot water 15 bar. Inner hose from 13 to 51 mm.**



**Technical information:**

**Inner hose:** black conductive EPDM.

**Cover hose:** black conductive EPDM - heat, abrasion and ozone resistant.

**Reinforcement:** high tensile textile cords.

**Temperature range:** water: -40°C to +210°C.

steam: +165°C

**Applications:** saturated steam and hot water delivery in general industrial applications.

**Producer:** Alfagomma (Italy)

**Hose length:** see in the table

350AA							
Code	Øin., mm	Øout., mm	Working pressure to steam, bar	Working pressure to water, bar	Bursting pressure, bar	Weight, kg/m	Coil length, m
STEAM-013-7-ALF	13	23	6	15	60	0,37	61
	16	26	6	15	60	0,42	61
STEAM-019-7-ALF	19	29	6	15	60	0,47	61
STEAM-025-7-ALF	25	35	6	15	60	0,58	61
	30	44	6	15	60	0,90	61
STEAM-032-7-ALF	32	46	6	15	60	0,95	61
STEAM-038-7-ALF	38	52	6	15	60	1.10	61
	40	54	6	15	60	1.15	61
STEAM-051-7-ALF	51	67	6	15	60	1.70	61

HIDROBALT

*Quality and reliability since 1995..*