

VULCANO PUH 09

Hose for suction of granulates, abrasive powders and sawdust. For plastic woodworking and ceramic industries, dedusting and suction plants. Inner hose from 38 to 305 mm



Technical information:

Inner hose: smooth, ester based polyuretane (PU).

Cover hose: corrugated, ester based polyuretane (PU).

Reinforcement: PU coated high adhesion steel wire.

Temperature range: -40°C to +90°C.

Applications: hose for suction of granulates, abrasive powders and sawdust. For plastic woodworking and ceramic industries, dedusting and suction plants.

Advantages: strong but very flexible even at low temperatures, is suitable to heavy duty applications where a very good abrasion resistance is required. Resistant to mineral oils, chemicals, atmospherical agents and ozone. Antistatic according to TRB S 2153 by grounding the spiral.

Producer: IPL (Italy)

Hose length: see in the table

VULCANO PUH 09						
Code	Øin., mm	Min wall thickness, mm	Vakuom, %	Bending radius, mm	Weight, kg/m	Coil length, m
VUL-PUH-040	40	0,9	50	50	0.32	20
VUL-PUH-051	51	0,9	40	60	0.44	20
VUL-PUH-063	63	0,9	30	70	0.53	20
VUL-PUH-070	70	0,9	30	80	0.68	20
VUL-PUH-080	80	0,9	30	90	0.78	20
VUL-PUH-090	90	0,9	25	100	0.87	20
VUL-PUH-102	102	0,9	20	120	0.96	15
VUL-PUH-120	120	0,9	15	140	1.14	15
VUL-PUH-127	127	0,9	15	150	1.38	15
VUL-PUH-140	140	0,9	10	160	1.51	15
VUL-PUH-160	160	0,9	10	180	1.72	15
VUL-PUH-180	180	0,9	5	210	1.73	15
VUL-PUH-203	203	0,9	5	230	1.93	15
VUL-PUH-254	254	0,9	3	290	2.40	10
VUL-PUH-305	305	0,9	2	350	3.27	10

If you can't find exact diameter – you need to ask